

# MATERIAL SAFETY DATA SHEET

Prepared December 9, 2004

## MANUFACTURER:

EASIWAY SYSTEMS INC.  
540 S River Street  
Delano, MN 55328

Business Phone: 1-763-972-6306  
Emergency Phone: 1-800-424-9300

## IMPORTANT:

Read this MSDS before handling and disposing of this product and pass this information on to employees, customers and users of this product.

---

### SECTION I - PRODUCT IDENTIFICATION AND USE

PRODUCT NAME: **EASISOLV 901**  
PRODUCT USE: SCREEN WASH  
CLASS: Organic Solvent mixture  
DOT SHIPPING NAME: Cleaning Compound, N.O.I.  
Not DOT regulated

### HMIS

Health: 1  
Flammability: 1  
Reactivity: 0  
Personal Protection: B

---

### SECTION II - COMPONENTS

	CAS #	%	OSHA PEL	ACGIH TLV
Non exempt solvent blend	Mixture	<60%	None Estab.	None Estab.

Complies with SCAQMD Rules 443.1 and 1171 for use in California.  
SARA - None of the ingredients are SARA reportable.

---

### SECTION III - PHYSICAL DATA

APPEARANCE & ODOR: Clear, colorless liquid - mild solvent odor.  
SPECIFIC GRAVITY: > 1.  
VAPOR PRESSURE: <1 mm Hg @ 20° C.  
VAPOR DENSITY: Heavier than air.  
VOC: 546 grams per liter, 4.56 lb./gallon.  
pH: Neutral.

---

### SECTION IV - FIRE OR EXPLOSION HAZARD

FLASHPOINT: >200° F PMCC.  
EXTINGUISHING MEDIA: Regular foam or water fog or CO<sub>2</sub> or dry chemical.  
UNUSUAL FIRE & EXPLOSION HAZARDS: On exposure to high temperatures, product may decompose and release toxic/flammable vapors.  
FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

## SECTION V - REACTIVITY DATA

STABILITY: Stable under normal conditions of storage and handling. Avoid heat, sparks, and open flames.

INCOMPATIBILITY: Oxidizing or reducing agents.

HAZARDOUS POLYMERIZATION: Will not occur.

---

## SECTION VI - HEALTH HAZARD DATA

ROUTE OF ENTRY: Inhalation, skin absorption and ingestion.

EFFECTS OF ACUTE EXPOSURE: Slight health hazard. Liquid contact can cause eye irritation and conjunctivitis; skin irritation and dermatitis.

EFFECTS OF CHRONIC EXPOSURE: Repeated or prolonged exposure may cause irritation, redness, burning, drying and cracking of the skin. High vapor concentrations may cause headaches, dizziness, anesthesia, drowsiness or chemical pneumonitis.

CARCINOGENICITY: No

TERATOGENICITY: No

REPRODUCTIVE TOXICITY: No

MUTAGENICITY: No

---

## SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

PERSONAL PROTECTIVE EQUIPMENT: Wear safety glasses or goggles and nitrile gloves when handling. Keep containers closed when not in use. Provide adequate ventilation in work area. An organic vapor respirator should be worn if needed.

LEAK AND SPILLS PROCEDURE: Stay upwind and away from spill. Keep all sources of ignition and hot metal surfaces away from spill. Use sand or other inert material to dam and contain spill. For small spills, use absorbent pads.

WASTE DISPOSAL: Dispose of in accordance with local, county, state and federal regulations.

**Do not weld, cut, braze or drill drums that are empty.**

---

## SECTION VIII - FIRST AID MEASURES

INHALATION (BREATHING): Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

EYE CONTACT: Irrigate immediately with water for at least fifteen minutes.

SKIN CONTACT: Wash off in flowing water. Wash contaminated clothing before reuse.

INGESTION (SWALLOWING): If swallowed, do not induce vomiting. Keep at rest. Get prompt medical attention.

---

## SECTION IX - ADDITIONAL INFORMATION

THE INFORMATION IN THIS MSDS WAS OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESS OR IMPLIED, REGARDING ITS CORRECTNESS. THE CONDITIONS OR METHODS OF HANDLING, STORAGE, USE AND DISPOSAL OF THE PRODUCT ARE BEYOND OUR CONTROL AND MAY BE BEYOND OUR KNOWLEDGE. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT.